



A brand of **TOTAL**

EVOLUTION 500 FT 15W-40



Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines

APPLICATIONS

Most recent technology engines

- Premium multi-grade motor oil for all engines, recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International Specifications

- API SN/CF

CUSTOMER BENEFIT

Excellent engine protection

- Improved engine cleanliness
- Very high anti-wear and anti-corrosion properties that maintain engine performance

Optimum performance

- Suitable for all driving conditions;
- Good thermal stability and good oxidation resistance
- Shear stability ensuring perfect lubrication in both hot and cold conditions

CHARACTERISTICS

EVOLUTION 500 FT 15W-40	Method	Units	SAE Grade 15W-40
Density at 15°C	ASTM D1298	Kg/m ³	874
Viscosity at 40°C	ASTM D445	mm ² /s	106
Viscosity at 100°C	ASTM 445	mm ² /s	14
Viscosity index	ASTM D2270	-	133
Pour point	ASTM D97	°C	-30
Flash point	ASTM D92	°C	251

The typical characteristics mentioned represent mean values