



A brand of **TOTAL**

# EVOLUTION 700 FT 10W-40



*Premium performance motor oil using ELF semi synthetic technology, intended for lubricating gasoline passenger car engines*

## APPLICATIONS

### Most recent technology engines

- Highest specification semi synthetic lubricant recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

### In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

## PERFORMANCES

### International Specifications

- API SN/CF

## CUSTOMER BENEFIT

### Excellent engine protection

- Outstanding protection against wear

### Optimal performance

- Advanced viscometrics for maximum power and minimum viscous drag
- Prevents sludge build-up and controls oxidation; Optimum power and performance under most severe driving conditions

## CHARACTERISTICS

EVOLUTION 700 FT 10W-40	Method	Units	SAE Grade 10W-40
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	866
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	102
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	14.7
Viscosity index	ASTM D2270	-	150
Pour point	ASTM D97	°C	-33
Flash point	ASTM D92	°C	238

The typical characteristics mentioned represent mean values