




SUPER SPORTI SM 15W40



Premium high performance multigrade oil for passenger car engine

APPLICATIONS

Gasoline / diesel engine cars

- A premium high performance multigrade engine oil formulated to provide wide temperature range engine protection than is required by ILSAC GF-4 or API SM/CF and is specially formulated to provide extra protection against the harmful effects of stop-and-go driving and high and low temperature engine operation.
- Recommended for all petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans.

PERFORMANCES

International Specification

- API SM/CF (API Service Symbol)
- ACEA A2-96 issue 3/B2-98 issue 2

Recommended for use

- Ford, GM, PSA, BMW, VW, Audi and Mercedes-Benz

CUSTOMER BENEFITS

Optimised performance

- High level of detergency/dispersancy minimizes low temperature sludge formation leading to cleaner engines.
- Unique innovation in lubrication technology, identify a way of offering total engine protection during the three stages of the drive cycle – start-up, warm-up and normal driving conditions.
- Freedom of ring sticking, reduction in deposits leading to a reduced engine wear and a longer engine and component life.
- Excellent thermal and oxidation stability.

Compatibility with a wide range of seal materials

- Ensures the important engine seals stay soft and pliable to minimize oil leakage.

CHARACTERISTICS

Elf Super Sporti SM	Method	Units	SAE 15W40
Volumetric mass at 15°C	ASTM D1298	kg/m ³	874
Viscosity at 40°C	ASTM D445	mm ² /s	104
Viscosity at 100°C	ASTM D445	mm ² /s	13.90
Viscosity Index	ASTM D2270	-	133
Pour Point	ASTM D97	°C	-30
Flash Point	ASTM D92	°C	220

The typical characteristics mentioned represent mean values

Elf Super Sporti SM 15W40
Version April, 2006

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.