

# ELF SUPER SPORTI XJ

## DESCRIPTION

# 20W50

**ELF SUPER SPORTI XJ** is a multigrade oil formulated according to the latest techniques for the most recent gasoline engines. Suitable for multi valves, naturally aspirated and turbocharged gasoline engines.

**ELF SUPER SPORTI XJ** exceeds the requirements of the following specifications :

- API : SJ / CF
- ACEA A3/B3
- VW 501.01/505.00
- MB 229.1

## APPLICATIONS

**ELF SUPER SPORTI XJ** passed the most severe tests concerning lubricants of the same category. It is particularly recommended for all gasoline engines (supercharged, injection, with or without overhead camshaft) of passenger cars and delivery vans operating under very severe conditions. Particularly recommended for engines using unleaded gasoline, including those fitted with catalytic convertors.

## PROPERTIES

**ELF SUPER SPORTI XJ** fulfills all the demands of superior level gasoline engine oils :

- \* Exceptional detergency and dispersancy maintaining a very high degree of cleanliness and preventing black sludge formation,
- \* Outstanding thermal and oxidation stability, preventing untimely damages,
- \* Remarkable protection against wear, particularly valve train wear,
- \* Extremely high viscosity index and shear stability because of the use of selected viscosity index improver ensuring very high performance in service,
- \* Maximum efficiency also demonstrated in unleaded gasoline powered type engines, and harmless to catalytic convertors.

## TYPICAL CHARACTERISTICS

CHARACTERISTICS	ELF SUPER SPORTI XJ 20W50
Specific gravity at 15°C	0.893
Kinematic viscosity at 40°C, mm <sup>2</sup> /s (cSt)	157
Kinematic viscosity at 100°C, mm <sup>2</sup> /s (cSt)	17.0
Viscosity Index	117
Pour Point, °C	-21
Flash Point, °C	220

Characteristics of this chart are indicative typical values

This lubricant, when used in accordance with our recommendation and for the application for which it is intended, does not constitute a special hazard  
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant



CHARACTERISTICS  
SHEET  
TFESEA240102