



ELF MOTO FORK OIL

10W
15W
20W

Elf Moto Fork Oil is the new range of high performance mineral fork oils.

APPLICATION

MOTORCYCLE FORKS AND SHOCK ABSORBERS

- Specially formulated to meet all the requirements of the different types of motorcycle telescopic forks and hydraulic shock absorbers.

APPROPRIATE GRADES

- The different grades are adapted to all types of machine (on or off-road), all conditions of use (solo or two-up) and different driving modes (touring or racing).

SPECIFICATIONS

MINERAL

- Formulas are based on selected "hydraulic quality" mineral oils

SAE 10 – 15 and 20W

- Extended viscosity range adapted to all applications.

CLIENT ADVANTAGES

ANTI-WEAR

- ELF MOTO FORK OILS consist of selected mineral bases fortified by special additives that give them many qualities, for example high anti-wear capability.

OPTIMUM ABSORPTION

- The oil ensures optimum absorption at all times of year, and this remains stable over time.

QUIK DE-AERATION

- Excellent performance with regard to air: limited foaming and rapid de-aeration

COMPATIBLE WITH ELASTOMERS

- Excellent compatibility with the elastomers used in motorcycle forks and shock absorbers.



CHARACTERISTICS

	10W	15W	20W	
Specific gravity at 15 °C	0.875	0.881	0.887	
Viscosity number	153	155	150	
Kinematic viscosity at 40 °C	47	72.6	99	mm ² /s
Kinematic viscosity at 100 °C	8.3	11.6	14.6	mm ² /s
Pour point	<-36	<-30	<-27	°C

(Typical values given for illustration)

This lubricant when used according to our recommendations and for the purpose for which it is intended presents no particular hazard

A safety data sheet complying with current EU legislation can be obtained from your local commercial advisor

21/01/02, cancels and replaces the issue of 18/05/01



ELF MOTO FORK OIL