



PERFO XC 30

Monograde oils designed for diesel engines in severe duty

APPLICATIONS

For diesel engines working under severe conditions

- Recommended for diesel engines, both naturally aspirated and turbo-charged in severe service.
- Designed for indirect injected diesel engine
- Provide good performance in gear and hydraulic systems designed to operate on this type of engine oils.

PERFORMANCES

International Specifications

- API CF/SF
- ACEA E2
- MIL-L-2104E

OEMS' Specifications

- DAIMLER CHRYSLER MB page 228.0
- MAN 270
- ZF TE-ML 02C/04B
- CATERPILLAR TO-2
- MTU OIL TYPE 1

CUSTOMER BENEFITS

Technical Profiles

- Excellent thermal behaviour
- Good alkalinity reserve
- High detergency and dispersancy for engine cleanliness
- Protection against rust and corrosion
- Excellent control of engine wear and deposits.

CHARACTERISTICS

Elf Perfo XC	Method	Units	SAE 30
Volumetric mass at 15°C	ASTM D1298	kg/m ³	890
Viscosity at 40°C	ASTM D445	mm ² /s	100
Viscosity at 100°C	ASTM D445	mm ² /s	11.50
Viscosity Index	ASTM D2270	-	99
Pour Point	ASTM D97	°C	-18
Flash Point	ASTM D92	°C	>200
TBN	ASTM D2896	mgKOH/g	11.2

The typical characteristics mentioned represent mean values

Elf Perfo XC 30
Version May, 2007

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.