




GEARELF 5 85W140



Extreme-pressure sulfophosphorated oils for gearboxes and axles

APPLICATIONS

Mechanical gearboxes and axles of cars and trucks

- These lubricants are parts of a modern range of products that are particularly suited to the most rigorous service conditions found in automotive mechanical transmission (light and heavy duty vehicles), agricultural machinery, civil engineering and handling equipment.
 - Mechanical gearboxes
 - Hypoid gear axles

PERFORMANCES

International Specification

- API GL-5
- US Military MIL-L-2105D

CUSTOMER BENEFITS

Technical profile

- Superior extreme-pressure, anti-wear and anti-scuffing properties that maintain a high level of efficiency in gears operating under heavy loads and subjected to repeated shocks.
- High resistance to deterioration, guaranteeing stable performances even in high working temperature.
- Anti-rust and anti-corrosion powers to protect steel and copper when in contact with water.
- Smooth shifting in manual transmissions by controlling glazing and coking of friction surfaces in synchronizing mechanisms.
- Neutral with regard to seals, even at high temperatures.
- Anti-foaming qualities.

CHARACTERISTICS

Elf Gearelf 5	Method	Units	SAE 85W140
Volumetric mass at 15°C	ASTM D1298	kg/m ³	910
Viscosity at 40°C	ASTM D445	mm ² /s	345
Viscosity at 100°C	ASTM D445	mm ² /s	25.00
Viscosity Index	ASTM D2270	-	92
Pour Point	ASTM D97	°C	-15
Flash Point	ASTM D92	°C	228

The typical characteristics mentioned represent mean values

Elf Gearelf 5 85W140
Version Sept, 2005

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.