

PRODUCT NAME
<b>PEAK Ecosyn Ultra VP 100</b>

DESCRIPTION & APPLICATIONS
<p>PEAK Ecosyn Ultra VP 50 is a fully synthetic vacuum pump oil formulated from selected Group IV PAO and Group III base stocks.</p> <p>PEAK Ecosyn Ultra VP 50 is suitable for all milking machine vacuum pumps and industrial vacuum pumps.</p>

FEATURES & BENEFITS
<p>PEAK Ecosyn Ultra VP 100's synthetic formulation allows it to give excellent lubrication at both high and low temperatures.</p> <p>PEAK Ecosyn Ultra VP 100 has excellent oxidative stability resulting in minimum deposit formation and longer oil life. It protects pump components from wear at any temperature and separates more readily from water than conventional mineral based vacuum pump oils would.</p> <p>PEAK Ecosyn Ultra VP 100 results in longer valve cleaning intervals as a result of high resistance to deposit formation and outstanding oxidative stability. Low wear as a result of excellent rust protection and high film strength.</p>

TYPICAL CHARACTERISTICS		
ISO Grade		100
Density		0.852
Viscosity @ 40° C	mm <sup>2</sup> /s (cSt)	98.5
Viscosity @ 100° C	mm <sup>2</sup> /s (cSt)	13.6
Viscosity Index	-	140
Flash Point Cleveland	COC °C	260
Pour Point	°C	-40

HEALTH / SAFETY & ENVIRONMENT
<p>Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.</p>

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing