

PRODUCT NAME
<b>JAY 460</b>

DESCRIPTION & APPLICATIONS
Jay 460 is a general purpose high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion and is suitable to be used as hydraulic oil where anti-wear performance is less critical.

FEATURES & BENEFITS
Jay 460 has excellent demulsibility and anti-foaming characteristics. The base oils and additives used in the formulation ensure that protection is provided against oxidation, corrosion and rusting and that machine performance is not effected by fluctuating temperatures. Jay 460 is suitable for use in circulating systems where silver plated components are found, as it does not contain zinc anti-wear additives.

SPEC'S & APPROVALS
Jay 460 meets the following performance specifications: ISO 460 AGMA 250.04 - rust & oxidization inhibited oils

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS		
Density @ 15° C, kg/L	ASTM D1298	0.902
Viscosity cSt @ 40° C	ASTM D445	440
Viscosity cSt @ 100° C	ASTM D445	30
Pour Point °C	ASTM D97	-12
Flash Point °C	ASTM D92	260

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.