

PRODUCT NAME
PEAK 25W70 SL/CF

DESCRIPTION & APPLICATIONS
PEAK 25W70 SL/CF is an exceptionally high viscosity multi-grade engine lubricant. It is formulated for use in worn and older style passenger vehicles, light commercials and other large 4 stroke engines, or where a high viscosity engine oil is preferred due to harsh operating conditions.

FEATURES & BENEFITS
PEAK 25W70 SL/CF is an excellent choice for older engines with high mileage. It will assist to increase oil pressure, control oil consumption, reduce engine noise, reduce oil burning and smoke emissions. PEAK 25W70 SJ/CFI will protect against oxidation, corrosion and wear all year round. It is suitable for use in extreme operating conditions such as heavy towing, rallying and racing. PEAK 25W70 SJ/CF can be used in engines operating on unleaded, lead replacement, LPG and diesel fuels.

SPECIFICATIONS & APPROVALS
PEAK 25W70 SL/CF meets the following performance specifications: Viscosity: 25W70 API: SL/CF ACEA A2/B2

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS		
Density @ 15° C, kg/L	ASTM D1298	0.898
Viscosity cSt @ 40° C	ASTM D445	255
Viscosity cSt @ 100° C	ASTM D445	27.5
Viscosity Index	ASTM D2270	138
Pour Point °C	ASTM D97	-19° C
Flash Point ° (COC)	ASTM D92	205° C

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing