

PRODUCT NAME
GAS ENGINE OIL

DESCRIPTION & APPLICATIONS
GAS Engine Oil is an advanced multi-grade engine lubricant that suitable to late model and older engines running on LPG/CNG and/or dual fuel. It is formulated to provide wide temperature range engine protection against starting friction and engine deposits. It offers extra protection against the harmful effects of stop-and-go driving and high and low temperature engine. It may also be used in late model passenger cars and light commercial vehicles operating on unleaded gasoline.

FEATURES & BENEFITS
The formulation used in GAS Engine Oil combats conditions associated with engines running on LPG/CNG fuels. It lubricates valve seats without excessive deposit build up, and through the use of appropriate base oils and viscosity index improvers it helps reduce oil consumption caused by higher operating temperatures. Advanced oxidation and corrosion inhibitors are used to protect copper-lead bearings that are affected by oil nitration and oxidation.

SPEC'S & APPROVALS
GAS Engine Oil meets the following performance specifications: SAE Viscosity: 15W40 ACEA A3/B3 API: SM/CF

TYPICAL CHARACTERISTICS		
Volumetric mass @ 15°C	Kg/m ³	882
Viscosity @ 40° C	mm ² /s	112
Viscosity @ 100° C	mm ² /s	14.5
Viscosity Index	-	142
Flash Point	°C	220
Pour Point	°C	-30

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing