PRODUCT NAME
PEAK SUPER ENGINE OIL

DESCRIPTION & APPLICATIONS

PEAK SUPER Engine Oil is a general purpose multi-grade engine oil for unleaded, lead replacement and LPG passenger vehicle engines. It is suitable for regularly serviced vehicles and the value conscious motorist. PEAK SUPER Engine Oil is best suited to vehicles manufactured before 1994.

FEATURES & BENEFITS

PEAK SUPER Engine Oil is formulated with the appropriate detergent, dispersant and anti-wear additives to provide protection of pre 1994 vehicles. It provides an acceptable compromise between cost and quality for engines requiring an API SH lubricant under moderate conditions. SUPER Engine Oil will protect against oxidation, corrosion and wear all year round. It is suited for use in engines operating on unleaded, lead replacement, LPG and diesel fuels.

SPEC'S & APPROVALS

SUPER Engine Oil meets the following performance specifications:

SAE Viscosity: 25W/50	API: SH/CD
MIL-L-46152D	CCMC G4,D4,PD2

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS

Density @ 15° C, kg/L	ASTM D1298	0.893
Viscosity cSt @ 40° C	ASTM D445	198
Viscosity cSt @ 100° C	ASTM D445	18.9
Viscosity Index	ASTM D2270	107
Pour Point °C	ASTM D97	-15° C
Flash Point ° (COC)	ASTM D92	210° C
TBN, mg KOH/g		7.5

Typical characteristics are only a guide to industry and are not necessarily

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing

Peak Lubricants Pty Ltd, ABN 74887510101

224-230 South Gippsland Hwy
Dandenong South,
3175, Victoria, Australia

T +61 3 9799 0977 • F +61 3 9799 7709
enquiries@peakoil.com.au
www.peakoil.com.au