

PRODUCT NAME
PEAK ATF DX3

DESCRIPTION & APPLICATIONS
PEAK ATF DX3 is formulated for use in automatic transmissions where Dexron® III, Dexron® II or Mercon® fluids have been specified. It is suitable for use with new technology transmission components and meets the need for improved fluid stability and reliability under increased operating temperatures.

FEATURES & BENEFITS
PEAK ATF DX3 is approved for a wide range of automatic and hydraulic transmissions. It may be used for complete service fills or top up where Dexron® III, Dexron® II or Mercon® fluids have been specified. Improved low temperature properties and excellent retention of frictional coefficient ensure consistently smooth shifts, both at cold start and under extreme operating conditions. Exceptional shear stable fluid qualities provide extended oil and component life. PEAK ATF DX3 provides protection of mobile hydraulic pumps such as those of Denison, Sperry Vickers and Sundstrand.

SPEC'S & APPROVALS
PEAK ATF DX3 meets the following performance specifications:
<ul style="list-style-type: none"> • General Motors Dexron® III (F30556) • Allison C4 • TASA • Ford Mercon® • Caterpillar TO-2 • PSF

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS		
Density @ 15° C, kg/L	ASTM D1298	0.853 kg/L
Viscosity cSt @ 40° C	ASTM D445	36 cSt
Viscosity cSt @ 100° C	ASTM D445	7.6 cSt
Viscosity Index	ASTM D2270	187
Pour Point °C	ASTM D97	-36 °C
Flash Point °	ASTM D92	194 °C
Appearance		Red Oily Liquid

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.