

PRODUCT NAME
MULTI DUTY 30

DESCRIPTION & APPLICATIONS
MULTI DUTY 30 is a high quality engine oil suitable for naturally aspirated and turbo charged four stroke diesel engines where a monograde oil is preferred. It may also be used in petrol engines where SAE 30 API SG oils are specified, and transmission applications requiring Allison C4 performance. MULTI DUTY 30 meets the requirements of many older engines such as Leyland, International Harvester, Gardner, Fiat and Bedford.

FEATURES & BENEFITS
MULTI DUTY 30 engine oil controls oil consumption, minimizes deposits and ensures protection from rust and oxidation. The formulation used will reduce wear on components leading to longer engine life. MULTI DUTY 30 is cost efficient mixed fleet oil for older engines requiring API CF/SG performance. It is also suitable for use in small petrol four stroke engines where SAE 30 oils are required such as stationary engines. Great oil for running in engines that have been reconditioned.

SPEC'S & APPROVALS
Multi Duty 30 meets the following performance specifications:
SAE: 30
MIL: MIL-L-2104D, E & F
DB /MB: 227.0 ,228.0
Japanese CD
Mack EO-K/2
API: CF-4/CF-2/CF/SG
ACEA: E2
Allison: C4/C3
Caterpillar TO-2

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS		
Density @ 15° C, kg/L	ASTM D1298	0.878
Viscosity cSt @ 40° C	ASTM D445	90
Viscosity cSt @ 100° C	ASTM D445	10.5
Viscosity Index	ASTM D2270	100
Pour Point °C	ASTM D97	-21
Flash Point °C	ASTM D92	>220
Sulfated Ash, %m	ASTM D874	<1.00

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.



Peak Lubricants Pty Ltd, ABN 74887510101



224-230 South Gippsland Hwy
Dandenong South,
3175, Victoria, Australia

T +61 3 9799 0977 • F +61 3 9799 7709
enquiries@peakoil.com.au
www.peakoil.com.au