



PEAKOIL

43 Kitchen Road Dandenong Victoria 3175

Ph: 03 9792 1999 Fax: 03 9794 7727 Email: ron@peakoil.com.au

PRODUCT NAME

BRAE 220

DESCRIPTION & APPLICATIONS

BRAE 220 is a high quality, High Viscosity Index (HVI) mineral based slideway oil. It is suitable to be used on slideways of the latest high precision machine tools, planers, lathes and guideways of other industrial equipment. BRAE 220 is non-corrosive and is compatible with cast iron, steel and all other modern plastic slideway materials.

FEATURES & BENEFITS

BRAE 220 is formulated with extreme pressure, anti wear, anti foam and tackiness additives. It will reduce chatter and stick-slip operation, and the tacky adhesion properties enable it to be used on both horizontal and vertical slideways. BRAE 220 has high film strength, which reduces contact and wear between slideway surfaces.

SPEC'S & APPROVALS

BRAE 220 meets the following performance specifications: ISO 220 Cincinatti Milacron: P50

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS

Density @ 15° C, kg/L	ASTM D1298	0.894
Viscosity cSt @ 40° C	ASTM D445	220 cSt
Viscosity cSt @ 100° C	ASTM D445	19.5 cSt
Pour Point °C	ASTM D97	-10° C
Flash Point °	ASTM D92	256 ° C

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.