



# Peak Lubricants Pty Ltd

224-230 South Gippsland Hwy Dandenong Victoria 3175  
Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

## PRODUCT NAME

**BRAE 68**

## DESCRIPTION & APPLICATIONS

BRAE 68 is a high quality, High Viscosity Index (HVI) mineral based slideway oil. It is suitable to be used on slideways of the latest high precision machine tools, planers, lathes and guideways of other industrial equipment. BRAE 68 is non-corrosive and is compatible with cast iron, steel and all other modern plastic slideway materials.

## FEATURES & BENEFITS

BRAE 68 is formulated with extreme pressure, anti wear, anti foam and tackiness additives. It will reduce chatter and stick-slip operation, and the tacky adhesion properties enable it to be used on both horizontal and vertical slideways. BRAE 68 has high film strength, which reduces contact and wear between slideway surfaces.

## SPEC'S & APPROVALS

BRAE 68 meets the following performance specifications:  
ISO 68  
Cincinatti Milacron: P47

## HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

## TYPICAL CHARACTERISTICS

|                        |            |         |
|------------------------|------------|---------|
| Density @ 15° C, kg/L  | ASTM D1298 | 0.888   |
| Viscosity cSt @ 40° C  | ASTM D445  | 68 cSt  |
| Viscosity cSt @ 100° C | ASTM D445  | 8.7 cSt |
| Pour Point °C          | ASTM D97   | -15° C  |
| Flash Point °          | ASTM D92   | 224 ° C |

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.

*Premium Quality Australian & Internationally manufactured lubricants for all industries*