

PRODUCT NAME
<b>POWER STEERING FLUID</b>

DESCRIPTION & APPLICATIONS
Power Steering Fluid is formulated for use in the majority of passenger car and light commercial power steering systems. It will provide smooth year round protection and will assist in preventing corrosion, oxidation, gear slippage and wear. Power Steering Fluid is dyed red for easy identification. <b>NOTE:</b> Do not use where specialist fluids are specified. E.g. Honda, SAAB, Mercedes benz.

FEATURES & BENEFITS
Power Steering Fluid is formulated with anti foam additives and corrosion and oxidation inhibitors. It is compatible with a wide range of seal materials and will protect metal components used in modern power steering systems. Power Steering Fluid can be used to top up existing fluids in power steering systems and is suitable to be used for year round performance.

SPEC'S & APPROVALS
Power Steering Fluid meets the following performance specifications: • General Motors Dexron® III (F30556)      • Ford Mercon®

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS		
Density @ 15° C, kg/L	ASTM D1298	0.87 kg/L
Viscosity cSt @ 40° C	ASTM D445	44.5 cSt
Viscosity cSt @ 100° C	ASTM D445	8 cSt
Viscosity Index	ASTM D2270	150
Pour Point °C	ASTM D97	-42 °C
Flash Point °	ASTM D92	193 °C
Appearance		Red Oily Liquid

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing