

PRODUCT NAME
<b>VACUUM PUMP OIL 68</b>

DESCRIPTION & APPLICATIONS
Vacuum Pump Oil 68 is manufactured using high quality solvent refined paraffinic base stocks. The blend formulation used was originally designed for use in Robinaire vacuum pumps, which were widely used in the refrigeration industry with vacuum readings of 0.01 mm/Hg. It is also suitable for general service in a wide range of vacuum pumps, particularly those associated with the refrigeration trade and milk industry. For best performance Vacuum Pump Oil 68 should be used in clean machines only.

FEATURES & BENEFITS
The high quality solvent refined paraffinic base stocks used to manufacture Vacuum Pump Oil 68 eliminate the possibility of vapour pressure increases that can be caused by additive introduced volatility. It has excellent filterability and water separation characteristics, and will offer good service life with minimal formation of deposits.

SPEC'S & APPROVALS
Vacuum Pump Oil 68 meets the following performance specifications: ISO Viscosity Grade: 68

HEALTH / SAFETY & ENVIRONMENT
Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS	
Density @ 15° C, kg/L	0.88
Viscosity cSt @ 40° C	67
Viscosity cSt @ 100° C	8.9
Viscosity Index	97
Pour Point °C	-9
Flash Point PMCC °C	>230

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing