



PEAK LOMA 15 XLT

PREMIUM SYNTHETIC HYDRAULIC OIL

DESCRIPTION & APPLICATION:

PEAK LOMA 15 XLT is a high-performance, low-temperature Hydraulic Oil formulated using high-quality Group 3 base oils with anti-wear, oxidation and corrosion inhibitors and anti-foam additives.

PEAK LOMA 15 XLT has been specially developed for medium to high pressure hydraulic systems operating in cool rooms or in cold climates where there is a wide variation in ambient temperature, such as in the construction, marine, mining and oil industries.

BENEFITS:

- High viscosity index and a low pour point ensures excellent low-temperature fluidity and provides excellent low-temperature start up, protecting the hydraulic system from wear and extending component life.
- Excellent wear and corrosion protection, ensuring good equipment life and decreased downtime.
- Enhanced air release and anti-foam properties that prevent cavitation.
- Excellent filterability to prevent filter blockages delivering increased filter life and reduced maintenance
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and improved equipment performance.

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
	20 Litre	
	205 Litre	

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.834
Kinetic Viscosity @ 40°C cSt	15.5
Kinetic Viscosity @ 100°C cSt	3.8
Viscosity Index	141
Pour Point °C	-45
Flash Point °C	>200
Colour	L 0.5

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Denison HF-0 / HF-1 / HF-2
- ✓ DIN 51 524 Part 3 (HLP type oils)
- ✓ Eaton Vickers 1-286-S, M-2950-S
- ✓ US Steel 136 / 127

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 27 July 2021



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982