



PEAK 85W140

PREMIUM MINERAL GEAR OIL

DESCRIPTION & APPLICATION:

PEAK 85W140 is a heavy-duty multi-grade gear lubricant containing extreme pressure additives formulated to provide the highest protection when operating in very severe conditions.

PEAK 85W140 for use in differentials fitted to modern-day passenger cars and light commercial vehicles, agricultural and industrial applications, suitable for gears including helical, spiral bevel and hypoid to minimize scuffing, welding, or galling tooth wear in severe load applications.

BENEFITS:

- Protection over a wide temperature range
- High quality extreme pressure additives for added protection under heavy load
- Good corrosion protection and rust prevention for longer component life
- Excellent wear protection

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.901
Viscosity 40°C cSt	280
Viscosity 100°C cSt	26.5
Viscosity Index	124
Flash Point °C	>215
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGM85140001	1 Litre	12
PKGM8514002.5	2.5 Litre	6
PKGM85140005	5 Litre	4
PKGM85140020	20 Litre	
PKGM85140060	60 Litre	
PKGM85140205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-5
- ✓ Rockwell 076
- ✓ Mack: GO-J
- ✓ Clark MS-8
- ✓ International Harvester B-22
- ✓ SAE J2360
- ✓ MS-0016
- ✓ US Military: MIL-L-2105 D

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 22 November 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982