



ICE BREAKER

PRODUCT INFORMATION SHEET

Description

ICE BREAKER eliminates diesel fuel freezing by reducing the diesel fuel's cold temperature gel point. It can be used in all diesel fuelled commercial transport, agricultural equipment, earthmoving and construction equipment, recreational 4WD's and stationary plant. It can also be added to "summer" diesel fuel in bulk storage conditions. The pour point of the fuel when treated with **ICEBREAKER** is reduced from 0°C to -6°C depending on the fuel treated to -13°C to -40°C depending on the treat rate. Test results in accordance with method IP15 have proven the following

Dilution Rate 1:500 pour point achieved -29°C
Dilution Rate 1;1000 pour point achieved -21° C
Dilution Rate 1;2000 pour point achieved -13° C

Advantages

- Minimises harmful emissions,
- Eliminates diesel freezing
- Improves fuel economy.
- Boosts Engine power.
- Economical means of treating diesel fuel in storage.
- Comes with money back guarantee
- Inhibits the growth of wax crystals in the fuel

Applications

Add Ice Breaker directly to the fuel tank and ensure a thorough mix for best results. 1 litre treats 2000 litres of diesel fuel and the product is prepackaged in an easy to use twin chamber bottle, allowing for graduated applications of 20ml (treats 40 litres) to 100 ml (treats 200 ltrs). It is important to add **ICEBREAKER** to the fuel at a temperature above the cloud point 5°C

Typical Characteristics

Appearance	Mobile coloured liquid
Colour (Visual)	Blue
Flash Point (°C)	>63 (Closed Cup)
Boiling Point (°C)	185

Available from



PEAK LUBRICANTS P/L

ABN: 74887510101

224-230 South Gippsland Hwy.

Dandenong VIC 3175

Ph: 9799 0977 Fax: 9799 7709



Available from



PEAK LUBRICANTS P/L

ABN: 74887510101

224-230 South Gippsland Hwy.
Dandenong VIC 3175

Ph: 9799 0977 Fax: 9799 7709

