



Peak Lubricants

224-230 South Gippsland Highway Dandenong Victoria 3175
Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

PRODUCT NAME

AC 68 COMPRESSOR OIL

DESCRIPTION & APPLICATIONS

AC 68 is a premium quality compressor oil specifically formulated to provide consistent lubrication, performance and protection of screw and rotary sliding vane compressors. It contains anti-wear additives along with rust, oxidation and foam inhibitors. AC 68 may be used in reciprocating type compressors or vacuum pumps where ISO 68 oil is required.

FEATURES & BENEFITS

AC 68 Compressor Oil has excellent chemical and thermal stability ensuring good service life of the lubricant and compressor components. It promotes exceptional cleanliness, demulsibility and filtering ability even when subjected to moisture / water contamination. The non-zinc based anti-wear additives used in the formulation provide high pressure and high-speed pump protection throughout all conditions. AC 68 Compressor Oil can assist in reducing equipment downtime and maintenance costs.

SPEC'S & APPROVALS

AC 68 Compressor Oil meets the following performance specifications:
ISO Viscosity: 68
- DIN 51506 (VBL, VCL, VDL)
- ISO / DP 6521 (DAA, DAB, DAG, DAH)

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS

Density @ 15° C, kg/L	ASTM D1298	0.88
Viscosity cSt @ 40° C	ASTM D445	68
Viscosity cSt @ 100° C	ASTM D445	8.7
Viscosity Index	ASTM D2270	99
Pour Point °C	ASTM D97	-9
Flash Point °C	ASTM D92	210

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.