



Peak Lubricants

224-230 South Gippsland Highway

Dandenong Victoria 3175

Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

PRODUCT NAME

ANTI SEIZE COPPER COMPOUND

DESCRIPTION & APPLICATIONS

Anti Seize Copper Compound is a NLGI Grade 1.5 bentone based grease product that provides lubrication for metal-to-metal parts allowing easy assembly and disassembly. It is suitable for use for industrial, automotive and marine applications where extreme conditions are found including high temperatures and corrosive environments. May be used as an anti-seize compound for extension drill bits, cylinder head gaskets, vehicle exhaust systems, brake linkages, and many other applications.

FEATURES & BENEFITS

Anti Seize Copper Compound will provide maximum protection in highly corrosive environments and in the most adverse temperature conditions. It is capable of protecting assemblies exposed to temperatures in excess of 900°C. The broad range of suitable applications in all conditions makes Anti Seize Copper Compound an excellent product to have available in workshops, tool rooms and engineering shops.

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS

NLGI Grade	1.5
Soap/Thickener type	Bentone
Colour	Flecked Gold
Worked Penetration @ 25°C	290 – 320 max
Drop Point °C	Does not melt
Base Oil	Paraffinic, oxidation stable
Viscosity cSt, 40°C	500
Viscosity cSt, 100°C	32
Solids Content, %wt	21

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.