



# Peak Lubricants Pty Ltd

224-230 South Gippsland Highway  
Dandenong Victoria 3175

Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

## PRODUCT NAME

**TORA 460**

## DESCRIPTION & APPLICATIONS

Tora 460 is a high quality extreme pressure ISO 460 industrial gear oil. It is suitable for use in enclosed gearboxes in industrial applications and may be used for plain bearings where high loadings or stresses are encountered.

## FEATURES & BENEFITS

Tora 460 industrial gear oil is formulated with advanced anti-corrosion additives to prevent problems arising from moisture/water contamination, even in high humidity conditions. Rapid demulsifying properties prevent the carry over of water and formation of emulsions, ensuring longer lubricant and gear component life. Tora 460 industrial gear oil contains anti-oxidation additives to protect against the effects of high thermal loading, commonly found enclosed gear-boxes.

## SPEC'S & APPROVALS

Tora 460 meets the following performance specifications:

ISO: 460

API: GL-4

U.S.Steel: 224

David Brown: S1.53.101(E)

AGMA: 9005-D94

DIN: 51517 (Part 3)

## HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

## TYPICAL CHARACTERISTICS

Density @ 15° C, kg/L	ASTM D4052	0.906
Viscosity cSt @ 40° C	ASTM D445	460
Viscosity cSt @ 100° C	ASTM D445	30
Pour Point °C	ASTM D97	-12
Flash Point °C	ASTM D92	275
Timken OK Load Value	ASTM D2782	60 lbs

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.