



Peak Lubricants

224-230 South Gippsland Highway

Dandenong Victoria 3175

Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

PRODUCT NAME

JAY 320

DESCRIPTION & APPLICATIONS

Jay 320 is a general purpose high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion and is suitable to be used as hydraulic oil where anti-wear performance is less critical.

FEATURES & BENEFITS

Jay 320 has excellent demulsibility and anti-foaming characteristics. The base oils and additives used in the formulation ensure that protection is provided against oxidation, corrosion and rusting and that machine performance is not effected by fluctuating temperatures. Jay 320 is suitable for use in circulating systems where silver plated components are found, as it does not contain zinc anti-wear additives.

SPEC'S & APPROVALS

Jay 320 meets the following performance specifications:
ISO 320
AGMA 250.04 - rust & oxidization inhibited oils

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS

Density @ 15° C, kg/L	ASTM D1298	0.899
Viscosity cSt @ 40° C	ASTM D445	310
Viscosity cSt @ 100° C	ASTM D445	24
Pour Point °C	ASTM D97	-9
Flash Point °C	ASTM D92	230

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.