



Peak Lubricants

224-230 South Gippsland Highway

Dandenong Victoria 3175

Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

PRODUCT NAME

JAY 68

DESCRIPTION & APPLICATIONS

Jay 68 is a general purpose high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion and is suitable to be used as hydraulic oil where anti-wear performance is less critical. It is suitable for vacuum pumps where a VG68 is specified.

FEATURES & BENEFITS

Jay 68 has excellent demulsibility and anti-foaming characteristics. The base oils and additives used in the formulation ensure that protection is provided against oxidation, corrosion and rusting and that machine performance is not effected by fluctuating temperatures. Jay 68 is suitable for use in circulating systems where silver plated components are found, as it does not contain zinc anti-wear additives.

SPEC'S & APPROVALS

Jay 68 meets the following performance specifications:

ISO 68

Hagglunds-Denison: HF-0

Vickers: M-2950-S, I-286-S

Cincinnati Milacron: P-68, P-69, P-70

DIN: 51524 HLP (Part 2)

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

TYPICAL CHARACTERISTICS

Density @ 15° C, kg/L	ASTM D1298	0.88
Viscosity cSt @ 40° C	ASTM D445	65
Viscosity cSt @ 100° C	ASTM D445	8.5
Pour Point °C	ASTM D97	-6
Flash Point °C	ASTM D92	210
Density @ 15° C, kg/L	ASTM D1298	0.88

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.