



Peak Lubricants

224-230 South Gippsland Highway

Dandenong Victoria 3175

Ph:(03)9799-0977 Fax:(03)9799-7709 www.peakoil.com.au

PRODUCT NAME

SOLVENT B

DESCRIPTION & APPLICATIONS

Solvent B is a wide boiling range, rapidly evaporating solvent widely used in the rubber industry. It is also used as a cleaning solvent in many applications and industries as it leaves no residue after use and evaporates rapidly.

TYPICAL CHARACTERISTICS

PROPERTY	TEST METHOD	UNIT	SPEC	TYPICAL VALUE
Distillation Range IBP FBP	ASTM D86	°C	50 max 130 max	45 120
Flash Point (Abel)	IP 170	°C	-	<0
Aniline Point	ASTM D611	°C	58-64	61
Density @ 15° C	ASTM D1298	Kg/litre	0.67-0.70	0.68
Benzene Content	GR 256	% v/v % m/m	0.07 max 0.09 max	0.05 0.07
Conductivity @23°C	ASTM D2624	PS/m	200-1000	450
Composition				
Paraffins		% m		73
Napthenes		% m		25
Aromatics		% m		2

HEALTH / SAFETY & ENVIRONMENT

Health, safety and environmental information is provided on the Material Safety Data Sheet for this product. Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications, and do not constitute any legal liability. Information is correct at time of printing.